



GAMA



# Air Driven Proportioning Unit evolution G-125 A



## Main Applications

- Insulation
- Water Proofing
- Cavity Filling
- Specialty Coatings

GAMA MACHINERY USA, INC.

# evolution G-125 A

**GAMA Proportioners represent the best and most efficient partner for high quality applications.**

## EVOLUTION

The **Evolution** series of exclusive designs are the result of an ambitious improvement process based on the experience and knowledge of the market's highest demands which has allowed the incorporation of important technical improvements that give the new units a reliable, high performance and maintenance friendly platform.



**A GAMA PROPORTIONER IS MUCH MORE THAN THE SUM OF ITS FEATURES!**

With the **Evolution G-125 A** model, you not only receive a compact and innovatively designed unit, you also receive additional features that will allow you to obtain higher productivity and excellent quality in your applications with complete reliability.

- Total warranty on parts for a period of two years.
- More than 20 years experience in the urethane industry.
- Immediate response to your questions.
- Specialists in technical assistance.
- Ability to adapt to your specific needs.

**GAMA** parts have been designed and manufactured with the same rigor, quality, and attention to detail as the Evolution units so that they perfectly match to support the most demanding application conditions.

## Quality stands out in the details!



## FEATURES AND CHARACTERISTICS

The new **Evolution G-125 A** air driven proportioning unit is of an advanced and compact design. It is specially aimed at the application of polyurethane foam in place. Its particular configuration facilitates easy access to all its components, simplifies the control functions and significantly reduces the maintenance work.

### Primary Heating System

The primary heating system consists of two separate hydraulically and electrically independent block heaters. Each heater incorporates 4 each 1250W (optional 1500W) heating elements that supply a total power of 5000W (optional 6000W) with the necessary control and safety features for the accurate and reliable performance of the system. The special design of the heaters allows for an input temperature of 100°F and enables it to reach application temperatures of 190°F in normal environmental temperature conditions.

### Hose Heating System

The hose heating system is designed with a 3000W isolation transformer that allows the heating of up to 310 ft of hose. The system incorporates an innovative concept of heated hose in which the copper resistance element is homogeneously spread around the hose. This allows accurate and uniform control of the application temperature of the products and avoids the heat concentrations that are produced in traditionally manufactured hoses.

### Control Panel

The control panel consists of a touch screen that incorporates specially designed software to facilitate the selection and control of all working parameters in a quick and easy manner. A sophisticated alarm system warns the operator of any error in the process to ensure the right application of the products. As an additional feature, a phase connection alarm is incorporated into the design to avoid costly repairs from errors or mistakes when plugging the proportioner into the electrical supply.

### Proportioning Pumps

The proportioning pumps are manufactured from high hardness tempered aluminium and treated with a layer of OAC+PTFE (patented process) that offers a low coefficient of friction, a high level of lubrication, and an increased level of wear resistance. The system includes a common guide system that ensures dynamic stability guaranteeing the correct alignment of the pump group and extending the life of the packing seals.

## TECHNICAL SPECIFICATIONS

Maximum Output	20 lb/min
Maximum Rated Pressure	1800 psi
Heating Power	10 Kw (12 Kw optional)
Hose Heating Power	3 Kw
Electrical (@ 10 Kw Htrs.)	43 amps @ 3 x 230 volts; 60 Hz
	55 amps @ 1 x 230 volts; 60 Hz
Electrical (@ 12 Kw Htrs.)	52 amps @ 3 x 230 volts; 50/60 Hz
	65 amps @ 1 x 230 volts; 60 Hz
Weight	275 lbs
Dimensions	H: 41 in. x W: 21 in. x D: 22 in

## GAMA MACHINERY USA, INC.

**WARNING:** the installation and operation of the described equipment should only be done by qualified personnel and strictly following the instructions included in the operating manuals. The information and data given on this brochure is considered to be correct; however, it should not be considered binding nor shall it constitute any explicit or implicit warranty or liability. On its constant effort to improve the design, features and performance of the equipment, GAMA MACHINERY USA, INC. reserves its right to make modifications without previous notice.